

DUPLEX 1400 to 15100

Basic-N Rooftop

All-purpose ventilation units
with cross-flow heat exchangers

DUPLEX 1400 to 15100 Basic are compact ventilation units with cross-flow heat recovery exchanger. They are solely intended for applications that do not come under the field of activity of the Committee's Regulation (EU) No. 1253/2014. DUPLEX Basic-N units are produced in compact (1400 to 10100 Basic-N) and semi-compact (12100 to 15100 Basic-N) version and contain two independently controlled EC fans with backward curved blades, a heat recovery exchanger with large heat-transfer surface and high efficiency, slide-out supply and exhaust air class Coarse 60 % (G4), ePM10 50 % (M5), ePM1 55 % (F7) filters, drain pans and possibly also an a circulation damper with a servo drive or integrated air heaters and coolers.

Unit casing is divided into two versions:

DUPLEX 1400-10100 Basic-N are frameless construction, casing is made of painted metal sheet with 30 mm PIR insulation with heat transfer coefficient ($\lambda = 0,024 \text{ W/mK}$).

DUPLEX 12100-15100 Basic-N are frame construction, casing is made of painted metal sheet with 45 mm mineral wool insulation with heat transfer coefficient ($\lambda = 0,037 \text{ W/mK}$).

DUPLEX Basic-N ventilation units meet the requirements of the most stringent European standards:

- Casing properties according to EN 1886
- EC motors according to ErP 2015
- SFP < 0,45 W/(m³/h) according to PassivHaus*
- Hygienic requests according to VDI6022

* in the defined working area



Advantages of DUPLEX Basic-N units:


- New design of ventilation units with excellent parameters
- Great thermal insulation of the casing (class T2)
- Reduced thermal bridging (class TB2)
- Filter side changing
- Elegant and efficient connections through the roof
- Compact dimensions
- Ease of installation
- Variable configuration of discharge ports
- Unified dimensions of ports
- Optional versions with a bypass and circulation damper
- High efficiency fans – SFP < 0,45 W/(m³/h)*
- High heat recovery efficiency of the cross-flow heat exchanger – up to 75 %
- Recessed junction box
- Integrated control system including temperature sensors
- Integrated web server (RD5 control system only)
- Comfortable unit control with touchscreen controller
- Comprehensive selection software
- Insulated duct extensions as an option

1400 to 15100 Basic-N


AVAILABLE MODIFICATIONS (CAN BE COMBINED)

- | | | | |
|-----|----------------------------------|-------|-----------------------------------|
| - B | with built-in bypass damper | - PT | with built-in preheater |
| - C | with built-in circulation damper | - CHF | with built-in direct chiller |
| - E | with built-in electrical heater | - CHW | with built-in water-based chiller |
| - T | with built-in hot-water heater | | |


OPERATING MODES OF DUPLEX BASIC-N UNITS



Ventilation with heat recovery with heating, cooling and preheating



Circulation heating or cooling



Ventilation without heat recovery (via bypass)

- ➔ e₁ ... Fresh outdoor air suction
- ➔ e₂ ... Fresh filtered air outlet

- ➔ i₁ ... Exhaust air suction
- ➔ i₂ ... Exhaust air outlet

- T, PT/E ... Central heating / electrical heater connection
- CH ... Cooling connection

SELECTION SOFTWARE



For the detailed design of DUPLEX series units, accessories and control systems we recommend using our dedicated design software. You can find it on our website at www.atrea.com or request a CD at our office.

Atrea[®]

UNIT VENTILATORS & HEAT RECOVERY

ATREA s.r.o., Čs. armády 32
466 05 Jablonec n. Nisou
Czech Republic



www.atrea.com

Tel: +420 483 368 111
Fax: +420 483 368 112
E-mail: export@atrea.com

PERFORMANCE GRAPHS

DUPLEX BASIC-N

DUPLEX Basic-N		1 400	2 400	3 400	5 400	7 100	8 100	10 100	12 100	15 100
Supply air – max. ¹⁾	m ³ h ⁻¹	1 700	2 900	4 500	6 200	8 300	8 800	11 000	12 600	16 000
Extraction air – max. ¹⁾	m ³ h ⁻¹	1 680	2 700	4 400	6 000	7 900	8 700	10 700	12 550	15 950
Heat recovery efficiency ²⁾	%	up to 75 %								
Number of versions and positions	-	see table "Mounting positions", page 4								
Weight ³⁾	kg	270-330	280-340	340-410	400-470	450-550	510-620	620-740	1 300-1 430	1 520-1 700
Max. power input	kW	0,6	1,2	2,7	4,8	6,5	7,7	10	10,5	12,3
Voltage	V	230			400					
Frequency	Hz	50								
Revolutions – max.	min ⁻¹	3 400	2 920	3 000	2 970	2 700	2 800	2 570	2 130	1 860
Heating output E low – max. ⁵⁾	kW	2,1	2,1	4,2	7,2	7,2	9,9	9,9	-	-
Heating output E high – max. ⁵⁾	kW	4,2	4,2	8,4	10,8	12,6	14,7	14,7	-	-
Heating output T – max. ⁴⁾	kW	20	27	34	51	64	76	94	104	110
Cooling output CHW – max. ⁴⁾	kW	12	18	25	35	51	60	68	77	85
Cooling output CHF – max. ⁴⁾	kW	11	15	18	31	48	58	65	74	82

¹⁾ Maximum flow rate through units at zero external pressure


²⁾ According to air volume

³⁾ Depending on equipment


⁴⁾ Depending on register type, liquid and flow rates

⁵⁾ For detailed information please use our DUPLEX selection software.


PERFORMANCE SUMMARY



HEAT RECOVERY EFFICIENCY




HEATING AND COOLING PERFORMANCES




BASIC DIMENSIONS


1400-10100 Basic-N
configuration 4/16





12100-15100 Basic-N
configuration 10/0 and 11/0



12100-15100 Basic-N
configuration 12/0 and 13/0



BASE FRAME (optional accessory) 1400-10100 Basic-N




DUPLEX Basic-N		1 400	2 400	3 400	5 400	7 100	8 100	10 100	12 100	15 100
Dimension H	mm	1 605	1 605	1 605	1 605	1 605	1 605	1 700	1 795	1 995
Dimension B	mm	555	555	685	770	990	1 170	1 390	1 620	1 790
Length L	mm	2 560	2 560	2 560	2 560	2 560	2 560	2 650	3 670 / 2998*	3 850 / 3050*
Length L1	mm	-	-	-	-	-	-	-	671	800
Length L2	mm	-	-	-	-	-	-	-	1 702	1 702
Length L3	mm	-	-	-	-	-	-	-	1 296	1 348
Dimension N	mm	130	130	105	105	105	105	105	-	-
Dimension U	mm	270	270	105	105	105	105	105	-	-
Dimension P	mm	135	135	105	105	105	105	105	-	-
Dimension J	mm	100	100	165	225	315	340	-	-	-
Dimension M	mm	155	155	185	205	265	355	350	-	-
Condensate drain	mm	ø 32								
Connecting ports										
Dimension X × Y	mm	300 × 300	300 × 300	400 × 400	400 × 400	500 × 500	500 × 500	700 × 500	900 × 710	900 × 710
Base frame										
Dimension D	mm	2 530	2 530	2 530	2 530	2 530	2 530	2 625	-	-
Dimension F	mm	1 545	1 545	1 545	1 545	1 545	1 545	1 670	-	-
Dimension E	mm	1 235	1 235	1 235	1 235	1 235	1 235	1 289	-	-
Dimension G (between holes)	mm	1 525	1 525	1 525	1 525	1 525	1 525	1 610	-	-
Dimension S	mm	659	659	459	459	259	259	344	-	-
Dimension Q	mm	289	289	189	189	89	89	202	-	-
Dimension T	mm	433	433	333	333	233	233	205	-	-

For detailed design and technical data we recommend using our dedicated selection software.

* For configuration 12/x and 13/x is L = L2 + L3

TYPES AND DIMENSIONS OF CONNECTING PORTS



INSTALLATION AND VERSIONS OF DUPLEX BASIC-N



INSTALLATION VERSIONS AND CONNECTING PORTS

DUPLEX 1400 to 15100 Basic-N units are available in a range of versions to facilitate their installation on the roof (outside). Rooftop units enable to go through the roof which is an excellent solution that saves material and labour costs in ducting and also

significantly saves the energy lost. DUPLEX units are characterised by a wide range of accessories – the ports may be optionally fitted with flexible flanges, duct extensions or special hoods if required.



MOUNTING POSITIONS

DUPLEX 1400-10100 Basic-N




* DUPLEX 5400-10100 Basic-N with max. one coil

DUPLEX 12100-15100 Basic-N



MOUNTING POSITIONS - CONNECTIONS THROUGH THE ROOF





HANDLING SPACE

DUPLEX units must be installed with the prescribed handling space around the unit in mind. Below the unit at least 150 mm must be left to install the DN 32

condensate drain line. This line must run through a U-bend at least 150 mm high into a sewer. Handling space in front of the unit must be maintained for replacing filters.

1400-10100 Basic-N




* only for units with built-in coil

handling space in front of the door

control manifolds

control modules



12100-15100 Basic-N

Type	T (mm)
DUPLEX 1400 Basic-N	600
DUPLEX 2400 Basic-N	600
DUPLEX 3400 Basic-N	700
DUPLEX 5400 Basic-N	800
DUPLEX 7100 Basic-N	1 000
DUPLEX 8100 Basic-N	1 200
DUPLEX 10100 Basic-N	1 400
DUPLEX 12100 Basic-N	1 600
DUPLEX 15100 Basic-N	1 700

ACOUSTIC POWER L_w AND ACOUSTIC PRESSURE $L_{D,1}$

Type	Working point	Acoustic power L_w [dB(A)]					Acoustic pressure $L_{D,1}$ [dB(A)] at distance of 3 m
		inlet e_1	inlet i_1	outlet e_2	outlet i_2	unit	
DUPLEX 1400 Basic-N	1 000 m ³ /h (200 Pa)	45	44	75	73	61	40
DUPLEX 2400 Basic-N	2 000 m ³ /h (200 Pa)	62	57	87	89	71	51
DUPLEX 3400 Basic-N	3 000 m ³ /h (200 Pa)	68	65	82	86	71	50
DUPLEX 5400 Basic-N	4 500 m ³ /h (200 Pa)	72	68	90	84	72	52
DUPLEX 7100 Basic-N	6 000 m ³ /h (200 Pa)	71	73	90	87	72	51
DUPLEX 8100 Basic-N	7 500 m ³ /h (200 Pa)	78	79	91	92	78	58
DUPLEX 10100 Basic-N	9 500 m ³ /h (200 Pa)	84	80	91	95	66	46
DUPLEX 12100 Basic-N	11 000 m ³ /h (200 Pa)	70	71	92	93	70	50
DUPLEX 15100 Basic-N	14 000 m ³ /h (200 Pa)	70	68	91	94	65	45

MODIFICATIONS

DUPLEX BASIC-N - BASIC UNIT

DUPLEX xxxx Basic-N



Basic configuration

DUPLEX 1400-10100 Basic-N


The compact unit consists of supply and exhaust centrifugal fans with electric motors in anti-vibration mounting, removable cross-flow air-to-air heat recovery core assembled from thin plastic plates, removable Coarse 60 % (G4), ePM10 50 % (M5) or ePM1 55 % (F7) supply and exhaust air filters, and a condensate pan with DN 32 flexible hose. Top doors enable easy access to all built-in components. Front doors for easy filters changing and control system access.

DUPLEX 12100-15100 Basic-N

The unit consists of 3 separate sections:

- 1 - supply free-wheel fan with electric motors in anti-vibration mounting, removable supply filter Coarse 60 % (G4), ePM10 50 % (M5) or ePM1 55 % (F7)
- 2 - cross-flow heat recovery exchanger with an electric motor, a belt pulley and a belt
- 3 - exhaust free-wheel fan with electric motors in anti-vibration mounting, removable exhaust filter Coarse 60 % (G4), ePM10 50 % (M5) or ePM1 55 % (F7)

A front door enables easy access to all built-in components and filters.



Fans

All units are equipped with high-efficiency fans (ebm-papst and Ziehl Abegg) with free-running impellers and backward curved blades. Whole range of DUPLEX 1400 to 15100 Basic-N fans meets the requirements of the European directive ErP 2015.

Me.xxx; Mi.xxx




Heat recovery exchanger

For every DUPLEX 1400-10100 Basic-N unit size are two heat recovery exchanger types available (K750.F and K750.G), that differs in heat recovery efficiency and pressure loss, for DUPLEX 12100 and 15100 Basic-N units is available single type K900.A.

K.750.X, K900.A


DUPLEX BASIC-N - MODIFICATION DESCRIPTION



By-pass ("B")

By-pass of the plate heat recovery core on supply air side. By-pass consists of an opposed-blade damper and an actuator. It is fitted next to the recovery core inside the unit; it does not increase size of the unit. The standard actuator is BELIMO 24 V; other types are available upon request.

B.x



Mixing damper ("C")

The mixing damper is used to mix exhaust and supply air. Circulation valve consists of an opposed-blade damper and actuator. It is fitted next to the recovery core inside the unit; it does not increase the size of the unit. The standard actuator is BELIMO 24 V; other types are available upon request.

C.x



Hot water heating coil ("T")

Built-in water-to-air three-row (possibly multi-row) heating coil; made of copper pipes and aluminum fins. Designed for systems up to 110 °C and 1,0 MPa. The coil is standardly equipped with flexible connection and a steam-gas capillary thermostat for freeze protection. Units in modification T (with heating coil) must be equipped with e, supply air shutoff damper; an actuator with spring-return function is recommended. A coil hydraulic kit for heating capacity control of RE-TPO4 or RE-TPO3 type can be supplied with the coil upon request.


T.x



Electric heating coil ("E")

Integrated electric heating coils consist of PTC (Positive Temperature Coefficient) cells; they are generally used to heat up supply air. By default, electric heating coils always include protective thermostats (operational as well as emergency with manual reset) and regulation module KM featuring power switching elements with so called "zero" switching function (SSR). Built-in electric heating coils are offered in the 1400-10100 Basic-N units in two power options (basic and powerful). For more information please refer to the selection software DUPLEX.


E.x



Direct expansion (DX) coil ("CHF")

A built-in coil made of copper pipes and aluminum fins, including a condensate pan with individual condensate drainage and a pressure switch for freeze alarm. Three- or multi-row coils with various evaporate temperature are chosen depending on capacity required, refrigerant type and air parameters. Optionally it is possible to deliver double-circuit evaporator in division 1:1 or 1:2, or completely atypical with needed capacity.

CHF.x



Chilled water cooling coil ("CHW")

A built-in coil made of copper pipes and aluminum fins, including a condensate pan with individual condensate drainage. Three- or multi-row coils are chosen depending on capacity required, cooling medium type and air parameters. The cooling coil can be equipped with the R-CHW2 or R-CHW3 hydraulic kit on request.

CHW.x



Integrated pre-heater ("PT")

Built-in water-to-air three-row heating coil; made of copper pipes and aluminum fins. Designed for systems up to 110 °C and 1,0 MPa. Non-freezing liquid must be used.

PT.x

OTHER OPTIONAL ACCESSORIES (BASIC OVERVIEW)

Ke.xxx; Ki.xxx

Shutoff damper e₁; i₂



Shutoff dampers standardly fitted with BELIMO actuators are located in the air inlet port. The following damper types are available:

- fresh air damper e₁ - mandatory for C modification (with mixing damper) and T, PT modification (with heating coil)
- exhaust air damper i₂

Fe.xxx; Fi.xxx

Air filtration



All DUPLEX Basic-N units can be equipped with supply or exhaust air filtration of ePM10 50 % (M5), ePM1 55 % (F7) classes instead of standard Coarse 60 % (G4) class. Pressure drop of the filter is then 50 to 100 Pa (clean filter) depending on air flow rate, unit type and dirt accumulated.

RE-TPO.x

Heating coil hydraulic kit



Its function is to control heating capacity of a heating coil. It consists of a three-speed pump, two globe shutoff valves and connection pipes. Further equipment depends on the type:

- RE-TPO4 - four-way mixing valve with an actuator for digital control system
- RE-TPO3 - three-way mixing valve with an actuator for digital control system

R-CHW.x


Cooling coil hydraulic kit



Its function is to control cooling capacity of a chilled-water cooling coil. It always consists of two globe shutoff valves and connection pipes. Further equipment depends on the type:

- R-CHW3 - three-way mixing valve with an actuator
- R-CHW2 - throttling valve with an actuator for digital control system

Hot water heating coil (TPO)



Separately supplied coil for installation into round duct. It is suitable for cramped locations, where it is impossible to put the coil inside the unit, as well as for rooftop units. The coil is standardly equipped with the steam-gas capillary thermostat.

Electric heating coil (EPO-V)



Separately supplied heating coil to be fitted into round or rectangular duct. Capacities and diameters can be found in respective catalogue sheets.

FK.x

Spare cartridge filters



Replacement filter cartridges in different sizes based on the unit type. Available in Coarse 60 % (G4), ePM10 50 % (M5), ePM1 55 % (F7) filtration classes.

H.P

Flexible connections



Ports can be equipped with flexible connections upon request.

CF.XXX

Constant air flow and pressure



Manometers reading fan pressure together with controls, enables intelligent fan control of preselected airflow. This accessory assumes the unit is equipped with ATREA digital control system. Using a second manometer (optional accessory) in the supply air duct enables the user to control constant pressure in the supply duct.

Insulated duct extension



Rectangular duct extension for connection through the roof. The casing is made from sandwich panels with mineral insulation. Standard length is 1 m.


MFF

Tube manometers



Accessory for filters for simple view of current pressure drop. The tube manometers are obligatory for hygienic unit design in accordance with the VDI 6022.

Base frame



Dismountable base frame with integrated PIR (30 mm) insulation and service doors. Standard height 500 mm, others on request. Available only for DUPLEX 1400-10100 Basic-N units.

Feet



The Basic-N units can be equipped with adjustable feet (alternative to base frame).

Special hoods



Special weatherproof hoods for inlet (e₁) and outlet (i₂) ports. The hood for e₁ port in combine with integrated droplet eliminator.

CONTROLS






DUPLEX Basic-N units are delivered with basic control components or with complete control systems.

There are three types of control systems available (Basic, CPM and RD5) according to customer needs and an application. The systems also include variety of sensors (temperature, humidity, air quality, CO₂) for effective operation control.

Features of the control systems

- selection of the most suitable and efficient control system at the lowest cost, depending on the application
- control system is integrated with the unit, most components are already wired and checked in factory, thus reducing the risk of incorrect wiring
- no control system project documentation is necessary for standard cases, standardized solutions can be used
- simple wiring, system simplicity, error indication
- qualified technical support and consulting

SUMMARY OF DUPLEX BASIC-N CONTROL SYSTEMS

Type	Use	Controller
Basic	<ul style="list-style-type: none"> - all electrical components are wired to a junction box terminal strip inside or outside the unit - standard components are fans, damper actuators, capillary freeze protection thermostat of hot water heating coil - more components are included upon customer's request (exact actuator type, sensors, thermostats, pressure switches etc.) - suitable for applications with separate delivery of control system; e.g. large buildings with central control system etc. 	<div style="text-align: center;"> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;"> basic version (fans, actuators, thermostats, pressure switches and others on request) </div> <div style="text-align: center; margin: 5px 0;"> ↑ ↓ </div> <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 0 auto;"> Supervisory control system </div> </div>
"RD5" controls	<p>Standard functions of the "RD5" controls</p> <ul style="list-style-type: none"> - EC fan speed control (based on selected mode) - automatic by-pass damper position (heat and cool recovery) - evaluates and prevents emergency limits based on measured temperature - ventilation and temperature weekly program setting - A web server and an Ethernet interface built in as standard connection for remote internet communication - inputs for switching using 230 V (4 inputs - 3 delayed, 1 instantaneous) - switch e.g. from bathrooms etc. - optional connection of CO₂ or RH sensor - max. 2 sensors with a switch or 0-10 V output - outputs for electric preheater and heater control (pulse 10 V) or hot-water control (0-10 V) <p>Additional RD-IO module</p> <ul style="list-style-type: none"> - optional manometer connection to ensure constant airflow control (see Constant airflow and pressure control on previous page) - constant pressure control - cooling control outputs (DX- or chilled-water cooling), possibly for a heat pump <p>Additional RD-K module</p> <ul style="list-style-type: none"> - additional inputs and outputs significantly extending control system functions <p>BACnet / KNX converter</p> <ul style="list-style-type: none"> - optional converter allowing connection to supervisory control system via BACnet or KNX protocol 	<p>CP Touch (touchscreen)</p>  <p>CP10RT</p>  <p>Web server (as standard)</p> 
"CPM" controls	<p>Standard functions</p> <ul style="list-style-type: none"> - EC fan speed control (stepless) - automatic by-pass damper position - frost protection of heat exchanger - switching of electric or water heater - input for external switch - inlet and outlet shut-off damper control - minimum and maximum fan speed preselection - analogue input (0-10 V) for air quality sensor (CO₂, RH) - outputs for controlling electrical preheater and heater (pulse switched 10 V) or water heater (controlled by 0-10 V signal) - outputs for controlling cooling (direct or water), eventually heat pump <p>Controller CPM</p> <ul style="list-style-type: none"> - fully graphic touchscreen - weekly program - "party" mode - "holiday" mode - filter change notice - automatic operation based on constant signal - e.g. constant pressure <p>Controller CP 10 RA</p> <ul style="list-style-type: none"> - rotatable controller 	 <p>CPM controller with touchscreen display</p>  <p>CP 10 RA with mechanical knob</p>